



Technical Data Sheet

<p>Article: 2321 teXXor topline</p> <p>Model: Nitrile-Gloves STULPE</p> <p>Sizes: 9, 10, 11</p> <p><small>For details on product dimensions and weights see below (table)</small></p> <p>Colour: beige/blue</p> <p>Material: Carrier material: cotton jersey Coating: nitrile (¾ coated)</p> <p>Packaging: 144 pair / carton</p> <p>Subpackaging: 12 pair, bundled</p> <p><small>Details of packaging are below mentioned (table)</small></p> <p>Care instructions:</p> <p></p> <p>PPE-category: Category II - includes mean risks not listed under Cat. I or III, according to Regulation (EU) 2016/425, Annex I (published in the Official Journal of the European Union)</p> <p>Standardize: <u>EN 420:2003+A1:2009 - Protective gloves - General requirements and test methods</u> <u>EN 388:2016 - Protective gloves against mechanical risks</u></p> <table border="0"> <tr> <td></td> <td>Abrasion resistance</td> <td>4</td> </tr> <tr> <td></td> <td>Cut resistance (Coupe test)</td> <td>1</td> </tr> <tr> <td></td> <td>Tear resistance</td> <td>2</td> </tr> <tr> <td></td> <td>Puncture resistance</td> <td>2</td> </tr> <tr> <td></td> <td>Cut resistance (TDM) according to EN ISO 13997:1999</td> <td>X</td> </tr> </table> <p><u>EN 13594:2015 - Impact protection</u> Test result: X</p> <p><small>(X = not tested)</small></p>		Abrasion resistance	4		Cut resistance (Coupe test)	1		Tear resistance	2		Puncture resistance	2		Cut resistance (TDM) according to EN ISO 13997:1999	X	 <p><small>© BIG Arbeitsschutz GmbH</small></p>
	Abrasion resistance	4														
	Cut resistance (Coupe test)	1														
	Tear resistance	2														
	Puncture resistance	2														
	Cut resistance (TDM) according to EN ISO 13997:1999	X														

Fittings:

Cotton jersey knit fabric, ¾ nitrile coating (blue), cuff, approx. 25 gauge (= 0,455 mm), thickness coating: approx. 0,85-0,100 mm

Characteristics:

Comfortable to wear and a secure grip, including when wet. Highly flexible and an excellent fit. Suitable for handling oils and lubricants. Excellent abrasion resistance.

Application:

Applicable for general work with medium risks and high requirements on abrasion, e.g. in the craft trade, construction sector, trade fair construction, automotive industry, mechanical engineering industry, steel industry, glass industry, food industry, agricultural sector

Additional information regarding purpose, applications and risk assessment:

These gloves satisfy the requirements of the quoted standards. Please note that the actual conditions of use cannot be simulated and that the decision on the glove's suitability for its intended purpose therefore lies exclusively with the user. The manufacturer is not responsible for improper use. Hence, an assessment of the residual risk should be performed before use in order to determine whether this glove is suitable for its intended purpose. Kindly note the printed pictograms and performance levels.

Precautionary measures during use:

- **These gloves must never be immersed in chemical substances or come into contact with chemical substances.**
- Only use gloves with a printed chemical pictogram when handling chemicals.
- Make certain that the selected glove is resistant to the chemicals being used.
- Do not use these gloves to protect against serrated edges or blades, etc.
- If gloves must be used in a hot environment, make certain that they satisfy the requirements of EN 407 and that they were tested as specified therein.



- Do not use the gloves close to moving machine parts.
- Check the gloves carefully before use to make certain there are no defects or imperfections.
- It is reasonable to assume that the gloves also protect against sharp objects such as injection needles, provided they satisfy the requirements of perforation resistance according to EN 388:2016.
- Discard damaged, worn, dirty or soiled gloves, irrespective of the substance (including on the inside), as they may lead to skin irritation and rashes. Consult a doctor or dermatologist should such cases arise.

EN 420:2003+A1:2009 - General requirements and test methods for gloves
EN 388:2016 - Protective gloves against mechanical risks:

Protective gloves against mechanical risks must achieve at least Level 1 or Level A in at least one of the properties (abrasion, cut, tear and puncture resistance) of the TDM cut resistance test according to EN ISO 13997:1999.

- Abrasion resistance: The number of cycles needed to wear through the test glove.
 Cut resistance: The number of text cycles in which the sample is cut through at constant speed.
 Tear resistance: The force needed to continue tearing the cut sample.
 Puncture resistance: The force needed to puncture the sample using a standardized test stylus.

EN 388:2016


4122X

Test criteria	Rating	Article 2321
A = Abrasion resistance	0 - 4	4
B = Cut resistance (Coupe test)	0 - 5	1
C = Tear resistance	0 - 4	2
D = Puncture resistance	0 - 4	2
E = Cut resistance (TDM) according to EN ISO 13997:1999	A - F	X
F = Impact protection test according to EN 13594:2015	P	X

The higher the test number, the better the test performance. X means 'not tested'. P means 'passed'.

Test	1	2	3	4	5
A = Abrasion resistance (number of abrasion cycles)	100	500	2000	8000	-
B = Cut resistance (index) Coupe test	1,2	2,5	5,0	10,0	20,0
C = Tear resistance (N)	10	25	50	75	-
D = Puncture resistance (N)	20	60	100	150	-

Test	A	B	C	D	E	F
E = Cut resistance according to EN ISO 13997:1999 (N)	2	5	10	15	22	30
Article 2321						

EN 13594:2015 - Impact protection:

Every area specified as providing protection against impact must be tested. The test method (dimensions of the test sample) does not permit impact testing of the finger protection. Gloves to protect against mechanical risks may be designed and manufactured in such a way that they offer specific impact damping (e.g. impact protection on the knuckles, the back of the hand, the palms). These gloves must satisfy the requirements of Level 1 according to EN 13594:2015.

The results of the Coupe test must only be taken as indications if blunting occurs during the cut resistance test (B), while the TDM cut resistance test (E) provides reference results in regard to performance.

WARNING:

The overall classification for gloves with two or more layers does not necessarily indicate the performance of the outermost layer. Gloves with mechanical resistance that achieve and demonstrate Level 1 tear resistance (C) or higher must not be worn if there is a risk of them catching when operating machines with moving parts. The tests refer to the palm of the gloves.

Markings on the gloves:

Trademark, art.-no. of manufacturer, size, CE-icon, at foodstuff suitability: glass and fork symbol, pictograms with the corresponding numbers of the relevant European PPE standards, i-mark, factory icon with date of manufacture: month/year



HANDSCHUHE >>



2321
10



Brand label of manufacturer

Article no. of the manufacturer

Size of gloves (example)

The CE marking confirms compliance with the requirements of European Regulation 2016/425.

i mark: Reference to the manufacturer's information.

Pictograms with the corresponding numbers of the relevant European PPE standards (example, detailed pictogram see previous pages).

Date of manufacture month/year: 00/0000

Dimensions/weights article:

Size	Length in cm	Width in cm	Height in cm	Weight in g
9	25	10,5	0,9	54
10	26	11,5	0,9	63
11	27	12,5	0,9	64

The above values are approximate and subject to slight variations.

Details of packaging unit:

Size	kg gross	kg net	Length in cm	Width in cm	Height in cm
9	19	17,5	58	26	55
10	19	17,5	58	26	55
11	19	17,5	58	26	55

The above values are approximate and subject to slight variations.

Hazardous ingredients - REACH (Registration, Evaluation, Authorization and Restriction of Chemicals):

The product is manufactured in compliance with Annex XVII of the European REACH regulation 1907/2006 and contains no hazardous substances in concentrations requiring declaration.

Declaration of Conformity

These gloves are classified as personal protective equipment (PPE). The CE mark confirms that the product satisfies the applicable requirements of Regulation (EU) 2016/425.

Identification and selection:

Selection of gloves must be made according to workplace requirements, type of hazard and relevant environmental conditions. The employer is responsible for choosing the right PSA. Therefore, it is necessary to check the suitability of the gloves for the needs needed before use.

Regulation for use:

The gloves fulfil the safety requirements only if they are worn in an entirely correct manner and in their best condition. Check the gloves for defects or flaws before use. If any tears or holes appear during use of the gloves, they must be disposed of immediately. Make sure that the gloves are not too large or too small and fit exactly. Modifications to this PPE are not permitted. Follow the instructions provided in the manufacturer's information and keep this information in a safe place during the entire service life of the PPE. We assume no responsibility for any damages and/or consequences resulting from improper use.

Washing Instructions:



Do not wash and bleach the gloves. Drying in tumbler is not possible. Do not iron. Professional dry and wet cleaning is not allowed.

Both new and used gloves must be checked carefully for any damage before they are worn, especially after cleaning. Never store dirty gloves if they are intended for reuse. In these cases, clean the gloves as thoroughly as possible before removing them, provided this does not present a serious danger. Severe soiling must be removed first. The gloves can then be cleaned with a non-aggressive detergent solution or rinsed in clean water then left to dry in a draft. Users are advised to carefully remove the gloves on the right and then the left if it is not possible to remove the soiling or if doing so would present a danger. Here, use the hand wearing the glove in such a way that the other glove can be removed without coming into contact with the soiling. The gloves may no longer display the same performance properties after cleaning. Hence, the manufacturer no longer accepts responsibility for the product after cleaning.





HANDSCHUHE >>

Storage and aging:

The gloves should be stored in their original packaging in a dark, cool and dry place, away from direct sunlight and away from any sources of heat. Prolonged contact with direct sunlight or excessive heat will shorten the service life. Avoid any contact of the product with solvents which could result in changes to the product or its properties. The service life is generally up to 3 years when used and stored properly (see also expiry date on the packaging). The dispenser boxes are also marked with the production date (month/year).

Disposal:

Used gloves may be contaminated with environmentally harmful or hazardous substances. Dispose of the gloves in accordance with applicable local laws.

Health risks:

Allergies, caused by the proper use of the gloves, are not yet known. If an allergic reaction still occurs, consult a doctor or dermatologist.

First Aid:

Remove the gloves if they are contaminated with hazardous materials.
In case of contact with skin: immediately consult a doctor if an allergic reaction occurs.
In case of eye contact: wash out the affected eye with water. Consult a doctor immediately.

The notified body responsible for the EU Type Examination:

CTC
Parc Scientifique Tony Garnier
4 rue Hermann Frenkel
69367 Lyon Cedex 07
France
(Identification No.: 0075)

For the full Declaration of Conformity and manufacturer's information, please visit:
www.big-arbeitsschutz.de



issued on 17.12.2018